







**Category** Interior use only IP20  
**Material** Machined Aluminium | Machined Brass  
**Canopy Finish** Brushed Aluminium | Rubbed Bronze | Black | White | Custom  
**System** Jack Plug Connector  
**LV Rating** 75W Max at 12V  
**LED Rating** 150W Max at 24V  
**Cut Out Hole**  $\varnothing 25\text{mm}$   
**Minimum Ceiling Void Depth** 20mm  
**Maximum Material Thickness** NA [surface mounted]  
**Distance Between Screws** 50mm  
**Accessories** Canopy | Solid Canopy | Plug  
**Weight** AL - 45g



Ceiling Material

The Flat Monopoint uses Precision Lighting's Jack Plug system recessed into a discreet ceiling plate, with power being fed from a remote or local transformer. It is available in standard brushed aluminium, rubbed bronze, black and white finishes, with custom finishes available on request. Ideal for use with a BESA box.

The Jack Plug system allows the luminaires to be easily removed for cleaning or relamping. The luminaires click into the Jack Plug socket, the threaded jacket then screws into position to lock the connection in place. Once fixed, the luminaires are free to rotate or alternatively, can be secured in place using two locking pins.



	LED Luminaires				LV Luminaires						
	Evo LED	Oculus	Discus	Pico	Evo	Evo S	Retro	Microspot	Radar	Rotor	Demilumen
	•	•	•	•	•	•	•	•	•	•	•
	•	•	•	•	•	•	•	•	•	•	•
	•	•	•	•	•	•	•	•	•	•	•
	•	•	•	•	•	•	•	•	•	•	•