



**Category** Interior use only IP20

**Material** Polycarbonate

**Finish** White


**Type** Electrical

**Voltage** 12V AC


**Weight** 150g - 550g

**Compatibility** Monopoints I Track Systems [up to 2m]


**Dimmable** Yes



PS75E-M - 75W | PS105E-M - 105W



PS150E-M - 150W | PS210E-M - 210W



PS255E-M - 255W | PS315E-M - 315W


Mode electronic transformers are suitable for use with our Monopoints and Track Systems up to a length of 3m. They are Class II, insulated against electric shock following direct and indirect contact. Supplied with terminal cover and cable retainer. Protected against overheating and short circuits, mains voltage spikes and overloads. These transformers are dimmable with leading and trailing edge dimmers.

**Notes**

For Toroidal transformers please see spec sheet PS-T.

For Relco transformers please see spec sheet PS-E-R.



MODE	POWER OUTPUT (VA)	VOLTAGE INPUT (V)	VOLTAGE OUTPUT (V)	FREQUENCY (Hz)	AMBIENT TEMP. (°C max)	CASE TEMP. (°C max)	WEIGHT (KG)	COLOUR	ORDER CODE
	75	240	11.8	50-60	55	90	0.15	WHITE	PS75E-M
	105	240	11.8	50-60	55	90	0.15	WHITE	PS105E-M
	150	240	11.8	50-60	50	90	0.40	WHITE	PS150E-M
	210	240	11.8	50-60	45	90	0.40	WHITE	PS210E-M
	255	240	11.8	50-60	45	90	0.55	WHITE	PS255E-M
	315	240	11.8	50-60	40	90	0.55	WHITE	PS315E-M